


NOTES:

1. PROVIDE PROPEX 2002, GEOTEXT 315ST, OR APPROVED EQUAL GEOTEXTILE WOVEN FABRIC. FABRIC SHALL EXTEND A MINIMUM OF ONE FOOT BEYOND THE LIMITS OF EXCAVATION.
2. OVER-EXCAVATE AREAS OF UNSUITABLE MATERIAL TO FIRM, SUITABLE SUBGRADE AS DIRECTED BY THE ENGINEER. BACKFILL WITH NO. 2 STONE (OR APPROVED EQUAL). STONE SHALL BE PLACED IN 12" LIFTS AND COMPACTED TO 95% OF THE MODIFIED PROCTOR DENSITY FOR THE MATERIAL. DEPTH AND WIDTH OF OVER-EXCAVATION WILL VARY WITH ACTUAL FIELD CONDITIONS.
3. ALL METHODS OF CONSTRUCTION SHALL BE IN COMPLIANCE WITH QUEEN ANNE'S COUNTY STANDARDS. ALL MATERIAL SPECIFICATIONS SHALL COMPLY WITH THE 2001 EDITION OF THE MARYLAND STATE HIGHWAY ADMINISTRATION'S "STANDARD SPECIFICATIONS FOR CONSTRUCTION MATERIALS" MANUAL AND ANY ADDENDUM THERETO.

APPROVED  DIRECTOR, DEPT. OF PUBLIC WORKS  CHIEF ROADS ENGINEER	SCALE: NO SCALE REVISIONS:	QUEEN ANNE'S COUNTY DEPARTMENT OF PUBLIC WORKS BIKE AND PEDESTRIAN PATH EXCAVATION OF UNSUITABLE MATERIAL
STANDARD NO. RD-104.04		